

TKSN-PROFI1400

TIEFKÜHLSCHRANK PROFI 1400 GN 2/1 - MIT 2 TÜREN

FEATURES

- AISI-430 stainless steel exterior, rear side galvanized panel.
- AISI-430 stainless steel interior with rounded corners.
- AISI-304 stainless steel inner side, press-formed supports + slides for GN 2/1 – GN 1/1 containers or shelves.
- AISI-304 stamped bottom.
- Doors with self closing system, blocked opening and magnetic gasket.
- GN 2/1 shelves made of plasticized steel wire, height adjustable.
- AISI-304 adjustable legs, 135 to 210 mm.
- Hinged front control panel.
- Fan assisted condenser unit.
- Fan assisted evaporator, with epoxi anticorrosion coating.
- Evaporator fan stops when door is opened.
- Automatic evaporation of defrost water.
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP.
- Digital temperature control, optimized defrost, high-temperature condensation alarm. Efficient management of energy consumption.



Length (mm)	Depth (mm)	Height (mm)	Capacity (L)	Cooling power (W)	Range	Climatic Class 2015/1094 EN16825	Coolant
1350	855	2115 - 2190	1121	907	-20°C -15°C	4 (30°C 55%HR)	R-290

TKSN-PROFI1400

TIEFKÜHLSCHRANK PROFI 1400 GN 2/1 - MIT 2 TÜREN

Temperature control	Digital
Evaporator	Epoxy finned block
Condenser	Finned block
Voltage / Frequence	230V / 50Hz
Nominal power	948 W
Insulation material	Polyurethane, 40 kg/m ³ density, zero ODP and GWP
Foaming agent	HFO
Exterior	AISI-430 stainless steel
Exterior rear side	Galvanized steel
Interior	AISI-430 stainless steel
Lighting	No
Number of shelves supplied	6 GN 2/1
Shelf dimensions (W x D)	650 mm x 530 mm

