

BTKS-PROFI700N

BÄCKEREITIEFKÜHLSCHRANK PROFI 700 EN

FEATURES

- AISI-430 stainless steel exterior, rear side galvanized panel.
- AISI-430 stainless steel interior with rounded corners.
- AISI-304 stamped bottom.
- Door with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense.
- Capacity for 60x40 shelves, containers or trays by stainless steel slides, 60 mm height adjustable.
- AISI-304 adjustable legs, 135 to 210 mm.
- Lifiable control panel.
- Fan assisted condenser unit.
- Fan assisted evaporator, with epoxi anticorrosion coating.
- Evaporator fan stops when door is opened.
- Automatic evaporation of defrost water.
- 60 mm sides isolement.
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP.
- Digital temperature control, optimized defrost, high-temperature condensation alarm. Efficient management of energy consumption.



Length (mm)	Depth (mm)	Height (mm)	Capacity (L)	Cooling power (W)	Range	Climatic Class 2015/1094 EN16825	Coolant
660	850	2115 - 2190	645	606	-20°C -15°C	5 (40°C 40%HR)	R-290

BTKS-PROFI700N

BÄCKEREITIEFKÜHLSCHRANK PROFI 700 EN

Temperature control	Digital
Evaporator	Epoxy finned block
Condenser	Finned block
Refrigerant	R-290
Voltage	230V 50Hz
Nominal power	520 W
Insulation material	Polyurethane, 40 kg/m ³ density, zero ODP and GWP
Foaming agent	HFO
Insulation thickness	60 mm
Exterior	AISI-430 stainless steel
Exterior rear side	Galvanized steel
Interior	AISI-430 stainless steel
Lighting	No
Number of shelves supplied	-
Shelf dimensions (W x D)	-
Numbers of slides set	20

