



Cucine elettriche

Electric ranges



La gamma di cucine elettriche SERIE 77 si compone di modelli 2/4 piastre, disponibili nella versione monoblocco (su armadio aperto e su forno statico elettrico) e nella versione top. Modularità: 40/70. Ottimo allineamento tramite coprigiunto.

Il piano di lavoro imbutito è in acciaio AISI 304 con spessore di 1 mm. Le piastre in ghisa (rotonde con diametro 145/220 mm o quadrate con dimensione 220x220 mm), a riscaldamento rapido con dispositivo di sicurezza contro il surriscaldamento, sono inserite nel piano "a tenuta" e sono disponibili in soluzioni di potenze da 1,5 kW e 2,6 kW con termostato di servizio a 6 (+1) posizioni per una regolazione ottimale della potenza. La versione con 4 piastre quadre ha una potenza di 2,6 kW per ogni

piastra. Lampade spia segnalano il funzionamento di ogni piastra sul pannello comandi. Gli spigoli raggiati e l'invaso stampato garantiscono il contenimento di liquidi e trascinazioni. I modelli con le piastre allineate al piano di lavoro hanno una potenza di 2,5 kW per ogni piastra; le piastre sono in ghisa con dimensione 300x300 mm. Versioni con forno elettrico GN2/1: camera di cottura in acciaio inox con base smaltata, porta in acciaio inox a doppia parete, intercapedine isolante e controporta in acciaio inox. Resistenze corazzate in acciaio inox da 5,3 kW, posizionate sul fondo e sul cielo della camera di cottura; regolazione termostatica della temperatura con doppio controllo separato fondo/cielo per una massima flessibilità di cottura.



The SERIE 77 electric range comprises models with 2/4 plates available as freestanding unit (on open cabinet and on electric static oven) or top versions. Modularity 40/70. Perfect elements connection by joint.

The watertight pressed worktop is in 1 mm AISI 304 stainless steel. The fast-heating hot plates with safety device to prevent overheating, made in cast iron (round with diameter of 145/220 mm, square with dimensions 220x220 mm) are watertight fixed to the worktop and are powered by 2,6 kW heating elements with 6 (+1) positions thermostat for optimized power control. The 4 squared plates version is powered by 2,6 kW heating elements per each plate. Indicator lights show when each hotplate is in operation.

Rounded corners and a moulded recess trap liquids and prevent overflowing, ensuring also easier cleaning. The models with the heating plates aligned with the worktop are powered by 2,5 kW heating elements. The heating hot plates are made in cast iron with dimensions of 300x300 mm. Versions with electric static oven GN 2/1: stainless steel double-wall cooking chamber with enameled bottom, stainless steel double-wall door with insulating casing.

5.3 kW stainless steel armoured heating elements placed on the bottom and on the top of the cooking chamber; thermostatic temperature control with separate bottom/top temperature control for maximum cooking flexibility.



Modello Model	Dimensioni esterne Exterior dimension	Dimensioni forno Oven dimension	Capacità piastre elettriche Capacity electrical plates			Forno Oven	Tot. kW	Alimentazione Power supply	Peso Weight
			1,5 kW	2,6 kW	2,5 kW				
	LxPxH cm	LxPxH cm				kW	kW		Kg
Su armadio On cupboard									
⚡ D77E2A	40x70x85	-	1	1	-	-	4,1	400V, 3N, 50/60	35
⚡ D77E2AQ	40x70x85	-	-	2	-	-	5,2	400V, 3N, 50/60	45
⚡ D77E2APQ	40x70x85	-	-	-	2	-	5	400V, 3N, 50/60	58
⚡ D77E4A	70x70x85	-	2	2	-	-	8,2	400V, 3N, 50/60	60
⚡ D77E4AQ	70x70x85	-	-	4	-	-	10,4	400V, 3N, 50/60	69
⚡ D77E4APQ	70x70x85	-	-	-	4	-	10	400V, 3N, 50/60	93
⚡ D77E6A	110x70x85	-	3	4	-	-	12,3	400V, 3N, 50/60	136
⚡ D77E6AQ	110x70x85	-	-	-	6	-	15,6	400V, 3N, 50/60	136
Su forno On oven									
⚡ D77E4F	70x70x85	56x66x31	2	2	-	5,3	13,5	400V, 3N, 50/60	90
⚡ D77E4FQ	70x70x85	56x66x31	-	4	-	5,3	15,7	400V, 3N, 50/60	99
⚡ D77E4FPQ	70x70x85	56x66x31	-	-	4	5,3	15,3	400V, 3N, 50/60	125
⚡ D77E4FVPQ	70x70x85	56x37x32	-	-	4	2,6	12,6	400V, 3N, 50/60	117
⚡ D77E6FAQ	110x70x85	56x66x31	-	6	-	5,3	20,9	400V, 3N, 50/60	140
TOP									
⚡ D77E2	40x70x25	-	1	1	-	-	4,1	400V, 3N, 50/60	20
⚡ D77E2Q	40x70x25	-	-	2	-	-	5,2	400V, 3N, 50/60	27
⚡ D77E4	70x70x25	-	2	2	-	-	8,2	400V, 3N, 50/60	40
⚡ D77E4Q	70x70x25	-	-	4	-	-	10,4	400V, 3N, 50/60	49











